


Compressing Large Data Sets with Geometry

PIs: Mathieu Desbrun (USC West)
Ronald DeVore (USC East)
Peter Schröder (Cal Tech)

Large Data Sets with Geometry

- Digital Elevation Maps
- Medical Imagery
- Computer Aided Design
- Reverse Engineering
- Steering Large Scale Computation

Surface: Graph of $2d$ -function



Encoders/Decoders

- **Server(Encoder)** \rightarrow **Client(Decoder)**

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$
- Client asks for surface

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$
- Client asks for surface
- $E_n(S) := \{b_1, \dots, b_n\}$

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$
- Client asks for surface
- $E_n(S) := \{b_1, \dots, b_n\}$
- Decoder: $D_n : B \rightarrow S_B$

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$
- Client asks for surface
- $E_n(S) := \{b_1, \dots, b_n\}$
- Decoder: $D_n : B \rightarrow S_B$
- Compressed Surface: $D_n(E_n(S)) := S_B$

Encoders/Decoders

- Server(Encoder) \rightarrow Client(Decoder)
- Encoder: $E : S \rightarrow B(S) = \{b_1, b_2, \dots, b_n, \dots\}$
- Client asks for surface
- $E_n(S) := \{b_1, \dots, b_n\}$
- Decoder: $D_n : B \rightarrow S_B$
- Compressed Surface: $D_n(E_n(S)) := S_B$
- if resolution is unacceptable client asks for more bits

Desirable Properties:

- Universal: Applies to all S

Desirable Properties:


- Universal: Applies to all S
- Progressive: Receiving more bits gives improved resolution

Desirable Properties:

- Universal: Applies to all S
- Progressive: Receiving more bits gives improved resolution
- Burn In: Client selects subregion; new bits only update chosen region


Burn-In

Coarse Approximation



Progressive Burn-In

Selected region for refinement



Desirable Properties:

- Universal: Applies to all S
- Progressive: Receiving more bits gives improved resolution
- Burn In: Client selects subregion; new bits only update chosen region
- Preserve Geometry and Topology

Desirable Properties:

- Universal: Applies to all S
- Progressive: Receiving more bits gives improved resolution
- Burn In: Client selects subregion; new bits only update chosen region
- Preserve Geometry and Topology
- Optimal: performs at best bit rate?
- Image Encoder: Cohen,Dahmen,
Daubechies,DeVore
- Burn In: DeVore, Johnson, Sharpley

How can we evaluate algorithms

- Experimental:

Encoders designed on heuristics

How can we evaluate algorithms

- Experimental:

Encoders designed on heuristics

- Precise Mathematical Formulation

Understand rules of game; what it means to be a winner

How can we evaluate algorithms

- Experimental:

Encoders designed on heuristics

- Precise Mathematical Formulation

Understand rules of game; what it means to be a winner

- Two essential ingredients

a. metric ρ to measure distortion

b. Precise definition of classes K_α to be compressed

Mathematical Formulation

- Distortion: $\rho(S, D_n E_n(S))$

Mathematical Formulation

- Distortion: $\rho(S, D_n E_n(S))$
- Evaluate Performance on a set K of surfaces

$$\delta(K; D_n, E_n) := \sup_{S \in K} \rho(S, D_n E_n(S))$$

Mathematical Formulation

- Distortion: $\rho(S, D_n E_n(S))$
- Evaluate Performance on a set K of surfaces

$$\delta(K; D_n, E_n) := \sup_{S \in K} \rho(S, D_n E_n(S))$$

- Given bit budget n

$$\delta_n(K) := \inf_{E_n, D_n} \delta(K, D_n E_n(S))$$

Mathematical Formulation

- Distortion: $\rho(S, D_n E_n(S))$
- Evaluate Performance on a set K of surfaces

$$\delta(K; D_n, E_n) := \sup_{S \in K} \rho(S, D_n E_n(S))$$

- Given bit budget n

$$\delta_n(K) := \inf_{E_n, D_n} \delta(K, D_n E_n(S))$$

- smallest distortion for the given bit budget

(Near) Optimal Encoding for K

- optimal

$$\delta(K, D_n E_n(S)) = \delta_n(K)$$

(Near) Optimal Encoding for K

- optimal

$$\delta(K, D_n E_n(S)) = \delta_n(K)$$

- near optimal

$$\delta(K, D_n E_n(S)) \leq C \delta_n(K)$$

(Near) Optimal Encoding for K

- optimal

$$\delta(K, D_n E_n(S)) = \delta_n(K)$$

- near optimal

$$\delta(K, D_n E_n(S)) \leq C \delta_n(K)$$

- Typically: $\delta_n(K) \approx n^{-s}$ for some $s > 0$

(Near) Optimal Encoding for K

- optimal

$$\delta(K, D_n E_n(S)) = \delta_n(K)$$

- near optimal

$$\delta(K, D_n E_n(S)) \leq C \delta_n(K)$$

- Typically: $\delta_n(K) \approx n^{-s}$ for some $s > 0$
- Game: Find encoder/decoder **E/D**: for all values of n and all classes K_α , encoder is near optimal

Optimal Encoding: Kolmogorov Entropy

- Given $\epsilon > 0$


Optimal Encoding: Kolmogorov Entropy

- Given $\epsilon > 0$
- Minimal ϵ cover: $K \subset \cup_{i=1}^{N_\epsilon} \mathcal{B}(S_i, \epsilon)$


Optimal Encoding: Kolmogorov Entropy

- Given $\epsilon > 0$
- Minimal ϵ cover: $K \subset \cup_{i=1}^{N_\epsilon} \mathcal{B}(S_i, \epsilon)$
- Kolmogorov Entropy $H_\epsilon(K) := \log_2 N_\epsilon(K)$

Covering



Covering



Kolmogorov Entropy

- Given $\epsilon > 0$
- Minimal ϵ cover: $K \subset \cup_{i=1}^{N_\epsilon} \mathcal{B}(S_i, \epsilon)$
- Kolmogorov Entropy $H_\epsilon(K) := \log_2 N_\epsilon(K)$
- $\delta_n(K) = \inf\{\epsilon : H_\epsilon(K) \leq n\}$

Optimal Encoding: Kolmogorov Entropy

- Given $\epsilon > 0$
- Minimal ϵ cover: $K \subset \cup_{i=1}^{N_\epsilon} \mathcal{B}(x_i, \epsilon)$
- $\delta_n(K) = \inf\{\epsilon : H_\epsilon(K) \leq n\}$
- Kolmogorov entropy of K gives our benchmark
- Usually not practical encoder

The Issues

1. The metric
2. The classes
3. Determine Entropy of Classes
4. Build near optimal Encoders/Decoders

Possible Metrics

- L_2 = Least squares not appropriate

Possible Metrics

- L_2 = Least squares not appropriate
- L_∞ better


Possible Metrics

- L_2 = Least squares not appropriate
- L_∞ better
- Hausdorff better yet

Comparison of Metric

- Offset by a lateral error of ϵ , L^∞ error may be **huge**


L^∞ metric error




Comparison of Metric

- Offset by a lateral error of ϵ , L^∞ error may be **huge**
- Hausdorff error is as expected

L^∞ metric error



Hausdorff metric error



Possible Metrics

- L_2 = Least squares not appropriate
- L_∞ better
- Hausdorff better yet
- $d(S, S') := \sup_{x \in S} \text{dist}(x, S')$

Possible Metrics

- L_2 = Least squares not appropriate
- L_∞ better
- Hausdorff better yet
- $d(S, S') := \sup_{x \in S} \text{dist}(x, S')$
- $\delta_H(S, S') := d(S, S') + d(S', S)$

Other Possible Metrics

- metrics to incorporate geometry/topology

Other Possible Metrics

- metrics to incorporate geometry/topology
- metrics to incorporate line of sight

Classification of Surfaces

- Classical Approach is smoothness spaces - too isotropic

Classification of Surfaces

- Classical Approach is smoothness spaces - **too isotropic**
- Classify according to complexity

Classification of Surfaces

- Classical Approach is smoothness spaces - **too isotropic**
- Classify according to complexity
- Complexity of Topology

Classification of Surfaces

- Classical Approach is smoothness spaces - **too isotropic**
- Classify according to complexity
- Complexity of Topology
- Complexity of Geometry

Classification of Surfaces

- Classical Approach is smoothness spaces - **too isotropic**
- Classify according to complexity
- Complexity of Topology
- Complexity of Geometry
- Differential Geometry to play crucial role

Classify Surfaces

- Critical points

Classify Surfaces

- Critical points
- ridge curves

Classify Surfaces

- Critical points
- ridge curves
- drainage curves

Classify Surfaces

- Critical points
- ridge curves
- drainage curves
- level curves

Classify Surfaces

- Critical points
- ridge curves
- drainage curves
- level curves
- plateaus

Classify Surfaces

- Critical points
- ridge curves
- drainage curves
- level curves
- plateaus
- smooth regions

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)
- We know how to do this by results in univariate approximation - free knot splines; n -term wavelets; optimal encoding

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)
- We know how to do this by results in univariate approximation - free knot splines; n -term wavelets; optimal encoding
- $\delta_n(U(B^\alpha)) \leq Cn^{-\alpha}$

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)
- We know how to do this by results in univariate approximation - free knot splines; n -term wavelets; optimal encoding
- $\delta_n(U(B^\alpha)) \leq Cn^{-\alpha}$
- Smoothness β between curves: how effectively can we approximate by interpolation

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)
- We know how to do this by results in univariate approximation - free knot splines; n -term wavelets; optimal encoding
- $\delta_n(U(B^\alpha)) \leq Cn^{-\alpha}$
- Smoothness β between curves: how effectively can we approximate by interpolation
- Classify S on basis of behavior of α and β

Classify on basis of the complexity of these curves

- each curve γ has a smoothness parameter $\alpha(\gamma)$: measures smoothness of γ in certain Besov spaces B^α corresponding to L_∞ (or Hausdorff)
- We know how to do this by results in univariate approximation - free knot splines; n -term wavelets; optimal encoding
- $\delta_n(U(B^\alpha)) \leq Cn^{-\alpha}$
- Smoothness β between curves: how effectively can we approximate by interpolation
- Classify S on basis of behavior of α and β
- Not ready to formulate this

Determine Entropy of Classes $K_{\alpha,\beta}$ in Hausdorff Metric

- Albert Cohen, Wolfgang Dahmen, Ingrid Daubechies

Determine Entropy of Classes $K_{\alpha,\beta}$ in Hausdorff Metric

- Albert Cohen, Wolfgang Dahmen, Ingrid Daubechies
- $\delta_N(K) \leq Cn^{-1}$ for K ball in $C(\Omega)$, $\Omega \subset \mathbb{R}^d$,
 $N = n^{d-1} \log n$


Determine Entropy of Classes $K_{\alpha,\beta}$ in Hausdorff Metric

- Albert Cohen, Wolfgang Dahmen, Ingrid Daubechies
- $\delta_N(K) \leq Cn^{-1}$ for K ball in $C(\Omega)$, $\Omega \subset \mathbb{R}^d$,
 $N = n^{d-1} \log n$
- $\delta_n(K) \leq Cn^{-1}$ for K ball in $BV(\Omega)$, $\Omega \subset \mathbb{R}$


Determine Entropy of Classes $K_{\alpha,\beta}$ in Hausdorff Metric

- Albert Cohen, Wolfgang Dahmen, Ingrid Daubechies
- $\delta_N(K) \leq Cn^{-1}$ for K ball in $C(\Omega)$, $\Omega \subset \mathbb{R}^d$,
 $N = n^{d-1} \log n$
- $\delta_n(K) \leq Cn^{-1}$ for K ball in $BV(\Omega)$, $\Omega \subset \mathbb{R}$
- $\delta_n(K) \leq Cn^{-2}$ for K class of continuous convex in $d = 1$.

box dimension



box dimension



Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves
- first bits for these selected curves (**first wire mesh**)

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves
- first bits for these selected curves (**first wire mesh**)
- choose additional next priority curves

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves
- first bits for these selected curves (**first wire mesh**)
- choose additional next priority curves
- predict these curves from first wire mesh:
generate smooth surface to first wire mesh

Designing Near Optimal Progressive Encoders


- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves
- first bits for these selected curves (**first wire mesh**)
- choose additional next priority curves
- predict these curves from first wire mesh:
generate smooth surface to first wire mesh
- update bits for all selected curves (**second wire mesh**)

Designing Near Optimal Progressive Encoders

- Extract critical points and curves capturing geometry and topology (**wire mesh**)
- Prioritize these curves
- Select a few highest priority curves
- first bits for these selected curves (**first wire mesh**)
- choose additional next priority curves
- predict these curves from first wire mesh:
generate smooth surface to first wire mesh
- update bits for all selected curves (**second wire mesh**)
- continue

Morse structure and Reeb graphs


Original terrain



Three Hills


Morse structure and Reeb graphs

Select critical points



Morse structure and Reeb graphs

Represent as graph




Three Hills

● Local Min/Max

● Saddle Points


Morse Structure



● Ground

Morse structure and Reeb graphs

Edge represents monotone region




Three Hills

● Local Min/Max

● Saddle Points


Morse Structure



● Ground

Morse structure and Reeb graphs

Edge represents monotone region




Three Hills

● Local Min/Max

● Saddle Points


Morse Structure



● Ground

Morse structure and Reeb graphs

Edge represents monotone region




Three Hills

● Local Min/Max

● Saddle Points


Morse Structure



● Ground

Morse structure and Reeb graphs

monotone region is a washer




Three Hills

● Local Min/Max

● Saddle Points


Morse Structure



● Ground

Morse structure and Reeb graphs

ground reference




Three Hills

● Local Min/Max


● Saddle Points

Morse Structure



Morse structure and Reeb graphs

Each saddle point gives level curve




Three Hills

● Local Min/Max


● Saddle Points

Morse Structure



Morse structure and Reeb graphs

prioritize by assigning weights




Three Hills

● Local Min/Max


● Saddle Points

Morse Structure



Morse structure and Reeb graphs


Definition of weight



Weight of Monotone Section
 $= F(z_1, z_2, Area_1, Area_2)$

Morse structure and Reeb graphs


removing low priority sections



● Local Min/M

● Saddle Point

Morse Structure



Add Geometry

- Morse structure captures topology

Add Geometry

- Morse structure captures topology
- Use curvature (shape operator) to select and prioritize geometry

Add Geometry

- Morse structure captures topology
- Use curvature (shape operator) to select and prioritize geometry
- embed geometry into graph

Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials

Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials
- interpolatory

Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials
- interpolatory
- shape preserving: monotonicity, convexity, etc

Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials
- interpolatory
- shape preserving: monotonicity, convexity, etc
- **optimal encoder for many classes (Besov balls):**

$$\delta_n(K_\alpha) \approx n^{-\alpha}, \quad K_\alpha := U(B^\alpha(L_\tau))$$

Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials
- interpolatory
- shape preserving: monotonicity, convexity, etc
- **optimal encoder for many classes (Besov balls):**

$$\delta_n(K_\alpha) \approx n^{-\alpha}, \quad K_\alpha := U(B^\alpha(L_\tau))$$

- K_1 includes all curves with finite arc length




Encoding Curves

- multiscale methods (**CAGD subdivision**) using piecewise polynomials
- interpolatory
- shape preserving: monotonicity, convexity, etc
- **optimal encoder for many classes (Besov balls):**


$$\delta_n(K_\alpha) \approx n^{-\alpha}, \quad K_\alpha := U(B^\alpha(L_\tau))$$

- K_1 includes all curves with finite arc length
- K_2 includes all convex curves

Simplest case - piecewise linear



Example: Level Curve Approximation



Further Efforts

- classify surfaces

Further Efforts

- classify surfaces
- determine Kolmogorov Entropy of these classes

Further Efforts

- classify surfaces
- determine Kolmogorov Entropy of these classes
- encode geometry

Further Efforts

- classify surfaces
- determine Kolmogorov Entropy of these classes
- encode geometry
- Burn In

Further Efforts

- classify surfaces
- determine Kolmogorov Entropy of these classes
- encode geometry
- Burn In
- Other Metrics

Predicting surface from wire mesh

- inpainting (nonlinear evolution equations)

Predicting surface from wire mesh

- inpainting (nonlinear evolution equations)
- constrained minimization

Predicting surface from wire mesh

- inpainting (nonlinear evolution equations)
- constrained minimization
- interpolation

Predicting surface from wire mesh

- inpainting (nonlinear evolution equations)
- constrained minimization
- interpolation
- constrained Delaunay

References

- A. Solé, V. Caselles, G. Sapiro, F. Arándiga, “Morse Description and Geometric Encoding of Digital Elevation maps,” preprint.
- H. Carr, J. Snoeink, U. Axen, “Computing contour trees in all dimensions, Proceedings of the 11th Annual ACM-SIAM Symposium on Discrete Algorithms, 918-926 (San Francisco, January 9 -11, 2000).
- A. López, F. Lumbreras, J. Serrat, J. Villanueva, “Evaluation of Methods for Ridge and Valley Detection,” IEEE Trans. Pattern Analysis and Machine Intelligence, **21.4** (1999), 327–335.
- M. McAllister and J. Snoeyink, “Extracting consistent watersheds from digital river and elevation data,” 1999 ASPRS Annual Conference.
- H. Edelsbrunner, J. Harer, A. Zomorodian, “Hierarchical Morse complexes for piecewise linear 2-manifolds,” *SCG'01*, June 3-5, 2001, Medford, MA.

References (cont.)

- A. Cohen, W. Dahmen, I. Daubechies, and R. DeVore, Tree approximation and optimal encoding, ACHA **11**(2001), 192–226.
- R. DeVore, B. Jawerth, and B. Lucier Image compression through wavelet transform coding, IEEE Transaction on Information Theory **38**(1992), 719–746.
- R. DeVore, B. Jawerth, and V. Popov, Compression of wavelet decompositions, American Journal of Mathematics **114**(1992), 737–785.
- R. DeVore, L.S. Johnson, C. Pan, and R. Sharpley, Optimal entropy encoders for mining multiply resolved data, in "Data Mining II", N. Ebecken and C.A. Brebbia (eds.), WIT Press, Boston, 2000, pp. 73–82.
- M. Meyer, M. Desbrun, P. Schröder, A.H. Barr, “Discrete differential geometry operators for triangulated 2-manifolds, preprint.
- B. Sendov, *Hausdorff Approximations*, Kluwer Academic Publishers Group, Dordrecht, 1990, pp. 364.